



# eFTE2

Gregg Young  
Warpstock Europe 2016

# What is it ?

- enhanced
- Folding
- Text
- Editor
  - VIO Version
  - PM Version



# Highlighting

- Plain/Text
- C
- e-mail
- HTML
- IPF
- Ada
- REXX
- MAKE
- FTE
- Win Resource
- DIFF
- MERGE
- SH
- PERL

# Highlighting

- PASCAL
- JAVA
- TEX
- BIN
- 4GL
- PHP
- Python
- ASM
- ASM 370
- TCL
- Fortran 90
- A51
- CLARION
- reST



# Highlighting

- EBFN
- SGML
- SIOD
- SLang
- Module 3
- Tex Info
- Merge
- Man pages
- Batch files
- Config.sys
- 63 Total

# Features

- Folding
- Column cut/paste
- Line edits
- Change case
- Search current word
- Match Parenthesis
- Split View



# Features

- Abbreviations

- C

- C OS2

- wswp = 'WinSetWindowPos';

- wcsv = 'WinCreateStdWindow'

- 37 total

- JAVA

- Perl

- REXX

- SH

# Features

- Change mode
- Change indent style
- C/C++
  - Watcom Help file from menu
  - OS/2 Programing guide from menu



# Commandline

- `-l line[,column]` Go to line (and column) in next file specified on command line
- `-m[MODE]` Use mode MODE for remaining files. If no argument is specified, mode override is canceled
- `-C` or `-![file]` Use specified configuration file (must be fullpath name). If no argument is specified, the default configuration, `edefault.fte`, is used.

# Commandline

- `-d[DEFINETERM]` Use this `DEFINETERM` for `%if()` statements in the config files. You can add your own to customize the configuration for individual projects. Currently eFTE includes `FM2`, `LINUXKERNEL`, `OS2DDK` and `GNU`. These change the indent style used at startup. Setting these in environment has the same effect.
- `-D[file.dsk]` Load/save desktop from file `file.dsk`. If no argument is specified, desktop loading/saving is disabled.



# Commandline

- `-H[file.his]` Load/save history from file `<.his>`. If no argument, disable history load/save.
- `-Ttags` Load tags file tags. The file must be in the format generated by the ctags program.
- `-ttag` Look up tag and display file containing it.
- `--` The rest of the arguments are not options, but filenames.

# Commandline

- `-+` The next argument is not an option even if starting with a '-'.  
`-+` is used to indicate that the following argument is not an option, even if it starts with a hyphen.
- `--help` `-h` or `-?` This show a usage dialog.
- `--debug` `--debugclean` These start logging --  
`debug` appends `efte.log` `debugclean` creates a new one.
- `--version` Provides some version information.



# Configuration Files

- My files
  - mymain.fte
  - systemmain.fte
  - myfontsize.fte

# Configuration Files

- Edit them in eFTE2 save but don't close
  - If you happen to break something you just fix it or undo and save again
- E:\EFTE\config\main.fte:13: Error: syntax error  
%if (!BSD\_BRACE)  
  
%define(1TBS  
  
Use: efte -! -l13 E:\EFTE\config\main.fte to  
repair error



# Changes from FTE

- On the fly compile of config files
- Fixed Regexp Search
- Fixed Search for All
- Consolidated all available configuration
- Additional command line switches
- Cleaned up the PMEFTE interface
- Numerous other minor fixes and enhancements

# Thanks

- Questions

